



AOV Louvre Windows



Louvre Windows

.....are Double glazed, louvre windows with thermally broken extruded aluminium frames. The horizontal louvres rotate on pivot bearings linked to a rack and pinion system, which ensures smooth, synchronised operation. With a maximum opening angle of 90 deg, these windows provide a large free area of ventilation compared to a standard windows..

Can be fitted directly into glazing system or builders opening.

Frameless louvres also available. Certified in accordance with EN 12101-2. For natural smoke and heat exhaust ventilation systems, NSHEVs. In addition to general ventilation applications we can also supply units for specialist smoke control use. The new SmoTec System has been fully tested and certified to EN 12101-2.

VOLTAGE SUPPLY

24 Vdc

STROKE

0-90 deg

ELECTRIC CONNECTION

2 wires

DOUBLE INSULATED

No

OPERATION

by polarity inversion

FORCE (PUSH ACTION)

1200 N

CURRENT ABSORPTION (WITH MAX LOAD)

0.65 A

PROTECTION CLASS

IP 54



Smoke Control Systems Limited Unit1 Cymbio Business Centre, Northway Lane, Tewkesbury, Glos. GL20 8JG
Tel:0844 499 6366 Fax:0844 499 6367 Email:info@smokecontrolsystems.co.uk www.smokecontrolsystems.co.uk